

MATERIAL SAFETY DATA SHEET

KIKR®

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY

PRODUCT NAME: Kikr (SB124-84G) EMERGENCY 24-HOUR PHONE NO. CHEM-TEL:
PRODUCT TYPE: Liquid Spray Calls from outside the US: 1-813-248-0585 (call
APPLICATIONS: Nail Care Products collect)
Calls from United States: 1-800-255-3924

SUPPLIER:
BACKSCRATCHERS SALON SYSTEMS, INC. EMERGENCY CONTACT IN EUROPEAN UNION:
9068 Elkmont Way TEL + 32 2 743 1540
Elk Grove, CA 95624 Avenue de Tervueren 300
1-916-686-2400 B-1150 Brussels, BELGIUM

2. COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT NAME	CAS NO.	CONTENTS	HEALTH (CLASS)	RISK (R NO.)
Ethyl Acetate	141-78-6	90-100%	F	R11/R22
Alkyl Toluidines	99-97-8	0-1%	Xn	R22

3. HAZARDS IDENTIFICATION

Highly flammable.

4. FIRST AID MEASURES

EYES: Irrigate with flowing water immediately and continuously for up to 15 minutes. Get medical attention immediately.

SKIN: Remove contaminated clothing and wash affected areas with soap and water.

INHALATION: Remove to fresh air. Obtain medical attention immediately if breathing is difficult.

INGESTION: Immediately give conscious patient two glasses of water then induce vomiting. Contact medical personnel immediately.

5. FIREFIGHTING MEASURES

EXTINGUISHING MEDIA: Dry chemical, foam or carbon dioxide.

UNUSUAL FIRE & EXPLOSION HAZARDS: Use water spray to cool fire-exposed containers, disperse vapors. Vapor is heavier than air and can travel considerable distance to a source of ignition and flashback. Material creates a special hazard because it floats in water.

PROTECTIVE FIRE EQUIPMENT: Firefighters should wear self-contained breathing apparatus and protective clothing.

6. ACCIDENTAL RELEASE MEASURES

SPILL CLEANUP METHODS: Eliminate ignition sources and avoid eye/skin contact. Dike/contain spill area. Place leaking containers in well-ventilated area with spill containment. Soak up with inert absorbent material. Avoid runoff into storm sewers and ditches that lead to natural waterways. Place into container for disposal.

WASTE DISPOSAL METHOD: Dispose of in accordance with local, state and federal EPA regulations. Hazardous Waste Code U112, D001.

7. HANDLING AND STORAGE

PRECAUTIONS - HANDLING: Highly flammable. Avoid heat, sparks and flames. Use only with adequate ventilation and avoid direct eye/skin contact. Wash hands/skin thoroughly after handling.

PRECAUTIONS - STORAGE: Closed containers exposed to temperatures above 120°F /49°C in transit or storage may develop excessive vapor pressure. Always open containers slowly to allow any excess pressure to vent. Store and use in a cool, well-ventilated area away from heat, sparks and flames.

OTHER PRECAUTIONS: Wash contaminated clothing before reuse. Discard contaminated leather clothing as waste. Wash hands well with soap and water after use.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

LT EXP	ST. EXP	INGREDIENT	CAS #	STD (8 hrs) (10 min)
		Ethyl Acetate	141-78-6	TWA 400ppm (1400mg/m ³)
		Alkyl Toluidines	99-97-8	NE (Not established)

PERSONAL PROTECTION: Safety glasses where direct eye contact is probable.

VENTILATION: Local exhaust where air concentration exceeds Long Term Exposure Limit.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Transparent Liquid
COLOR/ODOR: Colorless with fruity odor
SOLUBILITY IN WATER: Slightly soluble
SPECIFIC GRAVITY (WATER=1): 0.90
EVAPORATION RATE (BuAc=1): 4.5
FLASH POINT (METHOD): 25° F/ -4° C (TCC)
FLAMMABILITY LIMIT: LOWER: 2.0% **UPPER:** 11.4%

MELTING POINT (°F/°C): Not Established
BOILING POINT (°F/°C): 171° F/77° C
VISCOSITY (cps): <5
pH VALUE: Not Established
VAPOR PRESSURE @ 23° C (mm Hg): 73° F
VAPOR DENSITY (AIR=1): 3.0
VOLATILES (BY WEIGHT): about 90%

10. STABILITY AND REACTIVITY

STABILITY: Stable

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide

HAZARDOUS POLYMERIZATION: N/A

CONDITIONS TO AVOID: Heat, sparks and flame.

INCOMPATIBILITY (MATERIALS TO AVOID): Oxidizing agents such as hydrogen peroxide, nitric acid, perchloric acid or chromium trioxide.

11. TOXICOLOGY INFORMATION

ROUTE(S) OF ENTRY:

INHALATION: Move to fresh air as soon as possible. If breathing is difficult, seek medical attention. Vapors may be irritating to throat, mucous membranes & eyes.

SKIN: Flush contaminated area immediately with water. Remove contaminated clothing.

INGESTION: Seek immediate medical attention.

12. ECOLOGY INFORMATION

Considered to be a non-ozone depleting product according to current information. Avoid runoff into storm sewers and ditches that lead to natural waterways.

13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHODS: Dispose of in accordance with local, state and federal EPA regulations. Hazardous Waste Code U112, D001.

14. TRANSPORT INFORMATION

PROPER SHIPPING NAME: Ethyl Acetate

GROUND TRANSPORT: Consumer Commodity ORM-D

AIR TRANSPORT: Consumer Commodity ID 8000, PG II, Class 9

OCEAN TRANSPORT: Flammable liquid, Ethyl Acetate, Class 3, UN 1173, PG II, F/P -4° C

15. REGULATORY INFORMATION

RISK PHRASES: R11 Highly flammable.

R22 Harmful if swallowed.

SAFETY PHRASES: S16 Keep away from source of ignition - NO SMOKING.

S2 Keep out of the reach of children.

S46 If swallowed seek medical advice immediately and show container label.

S51 Use only in well-ventilated areas.

S9 Keep container in a well-ventilated place.

REGULATORY REFERENCES: Classification, packaging and labeling regulations. The Control of Substances Hazardous to Health Regulations 1988; Chemicals (Hazard Information & Packaging) Regulations 1993.

16. OTHER INFORMATION

GUIDANCE NOTES: The data contained herein is based upon information that Backscratchers believes to be reliable. Users of this product have the responsibility to determine the suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, express or implied, regarding accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof. For this and other reasons, we assume no responsibility and expressly disclaim liability for loss, damage or expense arising out of any way connected with handling, storage, use or disposal of the product. This MSDS was prepared expressly for this product. Use the materials only as directed. If the product is used as a component of other products, the information contained within this MSDS may not be applicable.

REVISION NOTES: Article 14

REVISION DATE: 6/25/08