

# MATERIAL SAFETY DATA SHEET

## EXTREME GLAZE SEALER

### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY

**PRODUCT NAME:** Extreme Glaze Sealer  
**PRODUCT TYPE:** Nail Lacquer  
**APPLICATIONS:** Nail Care Products

**EMERGENCY 24-HOUR PHONE NO. CHEM-TEL:**  
Calls from outside the US: 1-813-248-0585 (call collect)  
Calls from United States: 1-800-255-3924

**SUPPLIER:**  
BACKSCRATCHERS SALON SYSTEMS, INC.  
9068 Elkmont Way  
Elk Grove, CA 95624  
1-916-686-2400

**EMERGENCY CONTACT IN EUROPEAN UNION:**  
TEL + 32 2 743 1540  
Avenue de Tervueren 300  
B-1150 Brussels, BELGIUM

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT NAME	CAS NO.	CONTENTS	HEALTH (CLASS)	RISK (R NO.)
Acrylic copolymer (proprietary)		20-30%	F	R36/37/38
Butyl acetate	123-86-4	30-50%		R10
Butanone	78-93-3	30-40%	F, Xi	R11/36/37
N-Butyl phthalate	84-74-2	0-20%	Xi	R36/37

### 3. HAZARDS IDENTIFICATION

Highly flammable. Irritating to eyes and respiratory system.

### 4. FIRST AID MEASURES

**EYES:** Immediately flush eyes with water for 15 minutes. Seek medical attention if irritation persists.  
**SKIN:** Wash affected areas with soap and water. Remove contaminated clothing and launder before reuse. Seek medical attention if irritation persists.  
**INHALATION:** Move subject to fresh air. Give artificial respiration if breathing has stopped. Seek immediate medical attention.  
**INGESTION:** If swallowed DO NOT induce vomiting. Wash out mouth with water and give large quantities of milk or water to drink. Seek medical attention immediately and show container label. Never give anything by mouth to an unconscious person.

### 5. FIREFIGHTING MEASURES

**EXTINGUISHING MEDIA:** Alcohol foam, carbon dioxide, dry chemical, water spray.  
**FIRE HAZARDS:** Vapors are heavier than air and can travel to a source of ignition and flash back. Closed containers may rupture via pressure build-up when exposed to fire or extreme heat. Heated material can form flammable or explosive vapors with air.  
**PROTECTIVE FIRE EQUIPMENT:** Wear self-contained breathing apparatus and full protective gear.

### 6. ACCIDENTAL RELEASE MEASURES

**SPILL CLEANUP METHODS:** Eliminate all ignition sources including those beyond the immediate spill area. Ventilate the spill area. Evacuate the spill area. Avoid breathing vapor. Contain spills immediately with inert materials (sand, earth). Transfer spilled material to suitable containers for recovery or disposal. Prevent from entering sewer system or water supply.

### 7. HANDLING AND STORAGE

**PRECAUTIONS - HANDLING:** Avoid breathing vapors and skin contact. Do not handle material near food, feed or drinking water. Use non-sparking tools and grounding cables when transferring. Wash hands well with soap and water after use. Use in well-ventilated areas.  
**PRECAUTIONS - STORAGE:** Avoid all ignition sources. Store away from excessive heat, from sources of ignition and from reactive materials. Containers are hazardous when empty. Empty containers contain product residues.

### 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

INGREDIENT	CAS #	STD (8 hrs)	(10 min)
Acrylic copolymer (proprietary)		Not established	Not established
Butyl acetate	123-86-4	OSHA 100ppm	100ppm
Butanone	78-93-3	OSHA 200ppm	200ppm
N-Butyl phthalate	84-74-2	OSHA 5mg/m <sup>3</sup>	Not established

**PERSONAL PROTECTION:** Use and store in well-ventilated area away from ignition sources. Use respirator in areas with inadequate ventilation. Remove all contaminated clothing promptly. Wash exposed skin areas with soap and water. Use eye goggles with side shields to prevent eye contact.

**VENTILATION:** Local exhaust where air concentration exceeds Long Term Exposure Limit.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

**APPEARANCE:** Clear Liquid  
**MELTING POINT (°F/°C):** Not established  
**COLOR/ODOR:** Colorless with pungent, sweet odor  
**BOILING POINT (°F/°C):** 176° F/80° C  
**SOLUBILITY IN WATER:** 28%  
**VISCOSITY (cps):** 1000-4500  
**SPECIFIC GRAVITY (WATER=1):** 0.95  
**pH VALUE:** Not established  
**EVAPORATION RATE (BuAc=1):** >1  
**VAPOR PRESSURE @ 20C (mm Hg):** 70mm (estimate)  
**FLASH POINT (METHOD):** 25° F/-4° C (Setaflash Closed Cup)  
**VAPOR DENSITY (AIR=1):** >1  
**FLAMMABILITY LIMIT:** LOWER: 2.0% UPPER: 12.0%

### 10. STABILITY AND REACTIVITY

**STABILITY:** Stable  
**HAZARDOUS DECOMPOSITION PRODUCTS:** Oxides of carbon when burned.  
**INCOMPATIBLE MATERIALS:** Avoid contact with nitrates, chlorine, ammonia, strong oxidizers, alkalis & acids.

### 11. TOXICOLOGY INFORMATION

Material is possibly harmful if swallowed. Aspiration into lungs can produce severe damage and is a medical emergency. Ingestion may cause abdominal pain, nausea and diarrhea. Inhalation of vapor or mist can cause irritation of nose and throat, headache, nausea, dizziness, drowsiness, loss of coordination, lightheadedness, unconsciousness and coma in severe exposures.

### 12. ECOLOGICAL INFORMATION

Avoid allowing contaminated water to enter water supplies or fresh water.

### 13. DISPOSAL CONSIDERATIONS

**WASTE DISPOSAL METHODS:** For disposal, incinerate this material at a facility that complies with regulatory authorities in accordance with Federal, State and Local regulations.

### 14. TRANSPORT INFORMATION

**PROPER SHIPPING NAME:** Flammable liquid, NOS, contains butyl acetate, butanone.  
**GROUND TRANSPORT:** Consumer Commodity, ORM-D  
**AIR TRANSPORT:** Consumer Commodity, ID 8000, PG II, Class 9  
**OCEAN TRANSPORT:** Flammable liquid NOS, contains Butyl Acetate, Butanone, Class 3, UN 1993, PG II, F/P-4°C

### 15. REGULATORY INFORMATION

**LABEL FOR SUPPLY:** F (Highly flammable), Xi (Irritant)

**RISK PHRASES:**

R10 Flammable  
R11 Highly flammable  
R36/37 Irritating to eyes and respiratory system  
R38 Irritating to skin

**SAFETY PHRASES:**

S2 Keep out of the reach of children  
S9 Keep container in a well-ventilated place.  
S16 Keep away from sources of ignition - NO SMOKING.  
S25 Avoid contact with eyes.  
S33 Take precautionary measures against static discharges.

### 16. OTHER INFORMATION

**GUIDANCE NOTES:** The data contained herein is based upon information that Backscratchers believes to be reliable. Users of this product have the responsibility to determine the suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, express or implied, regarding accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof. For this and other reasons, we assume no responsibility and expressly disclaim liability for loss, damage or expense arising out of any way connected with handling, storage, use or disposal of the product. This MSDS was prepared expressly for this product. Use the materials only as directed. If the product is used as a component of other products, the information contained within this MSDS may not be applicable. °

**REVISION NOTES:** Article 10, 11, 14, 15  
**REVISION DATE:** 9/5/08